

Scala Line

		KE-300A	KE-250A	KE-200MD	KE-200TI	KE-150R	KE-100R	KE-200C	KE-400S
Gesamthöhe	mm	1225	1125	1125	1025	1125	300	160	725
Gehäusebreite	mm	195	165	135	135	160	160	450	280
Gehäusetiefe	mm	360	300	300	250	160	300	350	430
Bodenplatte B/T	mm	235/400	205/340	175/340	175/290	200/200			320/470
Gesamtgewicht	kg	41.3	30.8	23.4	19.1	13.4	7.1	11.2	
Gehäuse-Wandstärke	mm	25	22	19	19	19	19	19	25
Nettovolumen Bass	l	37.9	24.1	20.5	14.5	15.8	8.3	15.7	56.8
Nettovolumen Midr.	l	12.6	7.9	6	4.8				
Betriebssystem		teilaktiv	teilaktiv	passiv	passiv	passiv	passiv	passiv	aktiv
Prinzip Bass / Mid		BR / geschl.	BR / geschl.	BR / geschl.	BR / geschl.	BR	BR	BR	BR
Mehrwege-Prinzip	Weg	3	3	3	3	2	2	03. Feb	1
Woofer Nenngrösse	cm	30	25	20	20	13	13	13	38
Midrange Nenngrösse	cm	16	13	10	10			13	
Tweeter Nenngrösse	mm	25	25	25	25	25	25	25	
Verstärker-Leistung eff.	Watt	200	100						200
Belastbarkeit RMS	Watt	250	200	200	150	100	100	200	300
Minim. Verstärkerleist.	Watt	50	50	50	50	30	30	30	
Wirkungsgrad W/m	dB	93	92	91	90	89	88	91	95
U. Grenzfrequenz -3dB	Hz	20	25	25	30	35	40	40	15
O. Grenzfrequenz -3dB	kHz	40	40	40	40	40	40	40	110 Hz
Nennmpedanz	Ohm	4	4	4	4	4	4	8	10/2 k
Min. GS-Widerstand	Ohm	3	3	3	3	3	3	6	3
Trennfrequenz B-M	Hz	80	80	100	100				40-110
Trennfrequenz M-H	Hz	3000	3000	4000	4000	3000	3000	3000	
HG-Metallic-Lackierung	silver	x	x	x	x	x	x	x	x
Sockel 25mm Acrylglas	transp.	x	x	x	x	x			x
Bi-Wiring-Terminal	gold			x	x				
Schraub-Treminal	gold					x	x	x	